

SINGLE-BAG FILTER VESSEL RAFALE MR SERIES



FILTER TO BE FITTED WITH

One bag - Size 30 or 40 ►

GEOMETRY OF THE BAG

- Standard U bag ►
- W bag: 45% more surface area to filter higher flow rates or extend the lifespan of the bag
- Wide selection of felt, Monofilament or HP felt bags with O-ring (sheet FTQ/1PO/01E/A, pages 22-26)

DESCRIPTION

- Quick-open cover with swing bolts
- High-capacity filter
- Material: 316L stainless steel (wetted parts)
- Seal: Nitrile available as original equipment (Viton or EPDM available as spares See "Spare seals kit").
- Connections: pressed loose flanges
- **Operating conditions:**

Pressure: 10 bar max. at 100°C

ATEX marking: on request

_ _ _ _ _ _

OPTIONS

- Cover lifting davit
- Can receive an anti-return device, a magnetic system or a volume reducer (sheet FTQ/1PO/04E/A, page 29)
- ▶ W hold down ring to receive bags with W geometry
 - APPLICATION : Liquids, group 1 and 2 as per PED2014/68/EU

RECOMMENDED MAXIMUM FLOW RATE IN M³/H

| Coding | Bag size | Flow rate | |
|-----------------|-----------------------|-----------|--|
| VRAFALE1MRS6(P) | 30 Ø260mm L 860mm | 50 | |
| VRAFALE2MRS6(P) | 40 Ø260mm L 1070mm | 70 | |

Recommended flow rate for pressure drop of 0.150 bar Viscosity equivalent to that of water

- Felt bag, 1 to 100 µm
- Monofilalment bag, 5 to 1,000 µm

CODING SYSTEM



AS A MANUFACTURER, we can adapt the filters to your particular conditions. Our Design Office can design filters adapted to your usages.



DIMENSIONS AND CONNECTIONS

| Model | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) | H (mm) | Weight (kg) | Vol. (L) | Inlet/Outlet (E) (S) | Vent V | Drain P1 P2 |
|--------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|----------------|-------------|-------------------------|---------------|----------------|
| RAFALE I MR | 1285 | 1200 | 1050 | | 800 | / | | / | 41 | 90 | DN80 PN10* | Ø3/8" | Ø3/4" |
| RAFALE II MR | 1545 | 1460 | 1300 | 250 | 1100 | 1742 | 427 | 285 | 77 | 110 | DN100 PN10* | BSP female | BSP female |

*Pressed loose flanges





| SPARE PARTS | | | | | |
|-----------------------------------|----------------|--|--|--|--|
| Item | Article code | | | | |
| (4) U bag support for RAFALE 1 MR | 3SPTPRAFALE1S6 | | | | |
| (4) U bag support for RAFALE 2 MR | 3SPTPRAFALE2S6 | | | | |
| Swing bolt | 3BB14L65C | | | | |

EPDM * 3KIERAFALEMRWREC * EPDM seals: compliant with the requirements of the FDA, ACS and 1935/2004 EU

Material

FEP / Viton

Nitrile

Viton

+ 2 drain seals 3

Article code

3KINRAFALEMRREC

3KIVRAFALEMRREC

3KITRAFALEMRREC